Sale Name: August 2 Auction

LOT 368 - ECHOtape DC-M194A | Double-Sided Polyester Tape | Clear Thin Tape | All Weather/Cold Weather Insulation Mounting Tape | Superior Holding Power | 1.41 in x 60 yd 19



Retail Price 19
Condition Like New

Description

ECHOtape DC-M194A | Double-Sided Polyester Tape | Clear Thin Tape | All Weather/Cold Weather Insulation Mounting Tape | Superior Holding Power | 1.41 in x 60 yd 19

Model: DC-M194A Title: ECHOtape DC-M194A | Double-Sided Polyester Tape | Clear Thin Tape | All Weather/Cold Weather Insulation Mounting Tape | Superior Holding Power | 1.41 in x 60 vd Condition: Like New \$19 HIGH-PERFORMANCE ADHESIVE This permanent, thin double-sided tape has a specially engineered acrylic adhesive that s designed to work exceptionally well in cold temperatures. Versatile enough to work in many construction applications, this professional grade tape permanently bonds foams, plastics, metals, and other composite materials. SUPERIOR HOLDING POWER This extra-strength, permanent, double-sided tape provides superior holding power and durability from the onset. ALL-WEATHER HOLD Specially formulated as a cold weather, high-performance adhesive tape, this tape also performs well under a broad range of environmental conditions. The application temperature range for this tape is -4 F to 176 F, and the service temperature range is -40 F to 176 F. UV RESISTANT The PET carrier on this permanent, double-sided tape provides UV resistance. EASY TO HAND TEAR Hand tearable, this double-sided polyester film tape can be applied by hand or machine. FIELD TESTED AND TRUSTED BY PROFESSIONALS Metal building insulation contractors and commercial construction contractors commonly use this

high-performance, thin, double-sided tape. COMMON USES AND RECOMMENDED APPLICATIONS This thin double-sided polyester tape (PET tape) is often used for mounting metal building insulation. Commonly used to create lap seals on laminated insulation, reflective insulation, and jacketing insulation, this tape can also be used to mount smooth surface substrates in cold temperatures (such as freezers). STORAGE AND USAGE TIPS Always store the double-sided tape in its original packaging, away from direct sunlight. Apply to a clean surface, free from water, oil, dust, and other contaminants. For best results and optimum performance, use the tape within 12 months of purchase.

Quantity: 1



https://www.quarterpriceauction.com/